

Cloud-Based Disaster Monitoring Camera System

eT002

Watching over rivers, protecting lives.

Nationwide, over 2,500 river monitoring cameras—primarily for municipalities—have been deployed with our disaster prevention systems. Building on this extensive experience and knowledge, our latest model “eT002” has evolved into a more advanced camera system that incorporates direct feedback from the field.



Selected for the Tokyo Metropolitan Government’s “Advanced Disaster Prevention Technology Practical Application Support Project” (2015)

Point 1

Flexible System Configuration for Any Installation Environment

The compact system runs on solar power and LTE connectivity, enabling installation almost anywhere. Depending on site conditions, wireless LAN or wired LAN can also be used, and the system can be integrated with various sensors such as water level gauges.



NEW Image capture possible at intervals as short as 1 minute

NEW Remote maintenance
Monitor device status, check resources, and perform reboots

Intermittent operation reduces power consumption

Low-power system ensures up to 7 days of operation without sunlight

Point 2

Improved Nighttime Image Quality & Flexible Angle Adjustment

The system employs a proprietary high-sensitivity camera module, enabling clearer monitoring of river conditions at night without auxiliary lighting. It also features a varifocal lens, allowing flexible adjustment of the shooting range.

Nighttime Image Sample



NEW Minimum illumination improved from 0.02 lux (eT001s) to 0.005 lux, delivering near-daylight brightness even at night

NEW Equipped with a varifocal lens for wide-to-telephoto flexibility

NEW Automatic exposure adjustment tailored to monitoring targets

Integration with LED floodlights (Optional)

Point 3

Proven Reliability Backed by Extensive Track Record

In 2019, we joined MLIT’s “Innovative River Technology Project (Phase 3)”. As of March 2025, approximately 2,500 of our river monitoring cameras, developed in compliance with government specifications, are in operation both domestically and internationally.

National & Local Government Implementations

Tohoku Regional Development Bureau, Kanto Regional Development Bureau, Hokuriku Regional Development Bureau, Chubu Regional Development Bureau, Chugoku Regional Development Bureau, Kyushu Regional Development Bureau / Aomori Prefecture, Miyagi Prefecture, Yamagata Prefecture, Fukushima Prefecture, Niigata Prefecture, Tochigi Prefecture, Gunma Prefecture, Nagano Prefecture, Tokyo Metropolitan Government, Chiba Prefecture, Kanagawa Prefecture, Aichi Prefecture, Ishikawa Prefecture, Nara Prefecture, Mie Prefecture, Hiroshima Prefecture, Kagawa Prefecture, Ehime Prefecture, Kochi Prefecture, Fukuoka Prefecture, Oita Prefecture, Kumamoto Prefecture, Miyazaki Prefecture, Kagoshima Prefecture, Okinawa Prefecture / Iwamizawa City, Shikama Town, Yamagata City, Fukushima City, Niigata City, Nagaoka City, Kiryu City, Utsunomiya City, Katsushika Ward, Mitaka City, Fujisawa City, Odawara City, Sodegaura City, Abiko City, Kawaguchi City, Susono City, Fujiida City, Kanazawa City, Okazaki City, Wakasa Town, Konan City, Hashimoto City, Ise City, Otake City, Fuchu City, Ube City, Kurume City, Izuka City, Kumamoto City, Uto City, Soo City, Satsumasendai City, Nanjo City, and others.

Others

Including railway companies, solar power plants, private facilities, universities, research institutes, and more.

Overseas

Republic of the Union of Myanmar, Republic of the Philippines, People’s Republic of Bangladesh, and others.

Based on this proven track record and expertise, the latest model was developed with a focus on usability and enhanced functionality for river monitoring operations.

Stand Guard Disaster Prevention Cloud System

eT-Cloud

A cloud system that enables browsing, monitoring, and control of captured images. Reflecting feedback from municipal users and field operators, it continues to evolve into a more intuitive and user-friendly cloud platform.

Main Functions

Image Editing Function

Enables editing such as privacy masking, mosaics, and overlays, and allows embedding of site names, timestamps, and other information into images.

Download Function

Still images, time-lapse videos, and sensor data from a specified period can be downloaded.

Time-Lapse Video

Plays time-lapse videos created from captured still images.

Email & SMS Notifications

Sends alerts, such as threshold exceedance or flooding detection, to designated recipients.

Multi-Device Support

Automatically adjusts the layout for optimal viewing on PCs, smartphones, and other devices.

Digital Staff Gauge Optional

Displays a virtual scale on captured images, allowing approximate water level checks.

External Integration Optional

Provides APIs for supplying images and data externally, and allows automatic collection of images and data from external systems.

Auto-Patrol Display Optional

Designed for disaster control rooms and other large monitors, it automatically cycles through displays of selected monitoring stations.

Public Release Optional

A web application that makes stored images and data available to the public, equipped with load balancing to handle access surges during disasters.



Cloud Monitoring Screen
※Optional

Map-based view with installation locations and the latest captured images at a glance.



Auto-patrol display function
※Optional

Displays the latest information from each location in a slideshow format. Monitoring stations and display duration can be customized in detail.

Main Specifications

Main Camera Unit

Dimensions	W160×H174×D124mm (excluding brackets and protrusions)
Weight	Approx. 1.6kg (excluding brackets)

(Camera Section)

Image Sensor	1/2.8-inch CMOS
Effective Pixels	Approx. 2.13 million
Minimum illuminance level	0.005 lux
Output Resolution	VGA (640×480), HD (1280×720), FHD (1920×1080)
Lens Type	Varifocal Lens
Horizontal Viewing Angle	45–90° (adjustable at installation)

(Sensor I/O Section)

Serial Port	RS-485
Digital Input	2 inputs
Digital Output	2 outputs (including LED lighting control)

Solar Panel

Rated Maximum Output	27W or more
Dimensions	W538×H350×D35mm (excluding brackets and protrusions)
Weight	Approx. 2.8kg (excluding brackets)


Power Supply Box

Rated Voltage/Capacity	12V / 30Ah (capacity adjustable depending on installation conditions)
Dimensions	W300×H350×D250mm
Weight	Approx. 20.1kg (excluding brackets)

Environmental Performance

Operating Temperature	-20 to +50°C (camera), -10 to +50°C (power supply box)
Humidity	20–90% (non-condensing)
IP Rating	IP65 (camera unit)

Device Size & Dimensions (unit: mm)



NEW Expanded Camera Range of Motion | Easy connection with peripheral devices

Tilt range expanded from +15° upward to -50° downward

Two cable glands provided for simplified integration with external equipment



6F, Sorimachi Shoji Building, 1-3-5 Taito, Taito-ku, Tokyo 110-0016, Japan

+81-3-5246-4531 | eigyo-honsya@etrust.ne.jp

https://etrust.ne.jp